

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

H04B 1/08

(11) International Publication Number: WO 93/1859

(43) International Publication Date: 16 September 1993 (16.09.93)

US

(21) International Application Number: PCT/US92/10351

(22) International Filing Date: 3 December 1992 (03.12.92)

2 March 1992 (02.03.92)

(71) Applicant: MOTOROLA, INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).

(72) Inventors: HAMILTON, Robert, W.; 1133 Bayview Drive, Tsawwassen, British Columbia V4M 2R8 (CA). ZIBRIK, Larry, J.; 114-8751 General Currie Road, Richmond, British Columbia V6Y 3T7 (CA). (74) Agents: PARMELEE, Steven, G. et al.; Motorola, Inc., In tellectual Property Dept., 1303 E. Algonquin Road Schaumburg, IL 60196 (US).

(81) Designated States: CA, JP.

Published
With international search report.


(54) Title: PORTABLE COMMUNICATIONS DEVICE

(57) Abstract

(30) Priority data:

844,079

A portable communications device including a first and second housing (13, 15) pivotally connected by a hinge arrangement (30) and arranged for cooperatively containing wireless radio circuitry. The hinge arrangement (30) contains an integral antenna arrangement for coupling radio frequency signals to the wireless radio circuitry and thus the physical size of the portable communications device may be reduced.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

• •				_
AT	Austria FR	France	MR Ma	อบที่เอกโฉ
AU	Australia GA	Gabon	MW M	alawi
ВВ	Barbados GB	United Kingdom	NL No	etherlands
BE	Belgium GN	l Guinea	NO No	orway
BF	Burkina Faso CR	Greece	NZ N	ew Zealand
BC	Bulgaria HU	Hungary	PL Po	oland
BJ	Benin IE	Ireland	PT Po	ortugal
BR	Brazil IT	Italy	RO Ro	omania
CA	**Canada JP	Japan	RU R	ussian Federation
CF	Central African Republic KP	Democratic People's Republic	SD Su	ıdan :
CC	Congo	of Korea	SE Sv	weden
CH	Switzerland KR	Republic of Korea	SK SI	ovak Republic
Cl	Côte d'Ivoire K2	Kazakhstan	SN Se	enegal
CM	- Cameroon LI	Liechtenstein	SU So	oviet Union
cs	Czechoslovakia - LK	Sri Lanka	TD C	had
CZ	Czech Republic LU	Luxembourg	:TG Te	ogo
DE	Germany MG	C Monaco	UA U	kraine
DK	Denmark Me	3 Madagascar	us u	nited States of America
ES.	Spain MI		VN V	iet Nam
FI	Finland MI	N Mongolia		•

Portable Communications Device

Field Of The Invention

5

This invention relates to communications devices including but not limited to portable communications devices using radio frequency signals for communications.

10

20

Background Of The Invention

Generally, the demand for wireless communications has evolved to the point where portable equipment is highly desirable. At the same time the level of sophistication or complexity of the equipment, reflecting user demands and desires, has dramatically increased and a strong preference for smaller products has developed.

The above factors, among many, have created intense pressure on practitioners to invent smaller portable communications devices that may include comparatively large or bulky items such as batterys, antennas and user interface devices, for example, keypads, comparatively elaborate displays, etc. Responding to user needs and for various reasons, practitioners have invented portable communications devices which utilize multiple housings to contain the radio circuitry along with a battery and relatively large antenna arrangement. Using multiple housings may provide greater surface area for user interface devices such as keypads, displays, etc, and/or provide a cover and thus protection for user interface devices, and/or allow the physical dimensions of the portable device, such as a cordless telephone or portable data terminal to increase when the device is being interactively used. Practitioners have shown numerous ways of utilizing the multiple housings including mounting the

10

radio circuitry in one housing and the antenna in a second housing in for example, a cordless telephone.

In any event, given a multiple housing, some arrangement for, at least mechanically, connecting the multiple units together, as one, will ordinarily be required. This arrangement, typically a hinge, like the antenna and some user interface devices, may be comparatively large in order to provide the physical strength required to service and survive a portable communications device environment. This relatively large hinge, without more, is contrary to the essence of the requirements of a portable communications device, namely a small compact efficiently packaged unit.

Clearly a need exists to more efficiently utilize the physical space that may be occupied by the hinge and thus reduce the overall physical size of a portable communications device.

Summary Of The Invention

20 This invention addresses the aforementioned needs and problems by teaching a portable communications device including wireless radio circuitry for processing a radio frequency signal and a first and a second housings arranged and constructed for cooperatively containing the wireless radio circuitry, wherein the first and the second housing respectively include a first surface and a second surface disposed along an axis. Further included is a hinge apparatus, encompassing a volume disposed along the axis, that pivotally connects the first and the second surfaces such that the second surface pivots about the axis between a first position and a second position, wherein the first position allows substantially enhanced access to the first surface, and an antenna arrangement, disposed within the volume, for coupling the radio frequency signal to the wireless radio circuitry.

Brief Description Of The Drawing

The features of the present invention which are believed to be novel are set forth with particularity in the appended claims. The invention, itself, however together with further advantages thereof, may best be understood by reference to the accompanying drawing, FIG. 1, of a portable communications device constructed in accordance with the present invention.

10

30

Detailed Description Of A Preferred Embodiment

The drawing is representative of a portable communications device and includes wireless radio circuitry (11), that may, as depicted, be mounted on a substrate such as a printed circuit board, and is used for processing a radio frequency signal. The radio circuitry (11) is contained within a first housing (13) and a second housing (15) that have been arranged and constructed for cooperatively containing the wireless radio circuitry (11).

The first housing (13) includes a first surface (17) and the second housing (15) includes a second surface(19). The first surface (17) includes at least one edge (21) and the second surface includes at least one edge (23), such that the edges (21, 23) are disposed along, substantially parallel with, an axis (25). In practice, the surfaces (17, 19) may be used for mounting user interface devices such as a keypad (27) or display (29).

A hinge arrangement (30) is utilized to pivotally connect the second housing (15) to the first housing (13) about the axis (25). The hinge arrangement (30) is disposed along the axis (25) and encompasses a volume (31). Pivoting the second housing (15) about the axis (25) from a first position (33), as depicted, to a second position (35), for example through a 180° rotation, will substantially limit user access to the first and the second

5

10

Augustus mot in

surfaces(17, 19). Correspondingly, returning the second housing (15) to the first position (33) will expose the first surface (17) and the second surface (19) and allow substantially enhanced access to the first surface (17) as well as the second surface (19). This access will allow the user to operate the portable communication device, whereas the lack of access may correspond to protecting the user interface devices from inadvertent activation or damage and/or a desired reduction in physical dimensions.

An antenna arrangement (37) is disposed within the volume (31). The antenna arrangement (37) couples the radio frequency signal(s) to the wireless radio circuitry by for example, inductively coupling the radio frequency signal via inductor (39). Depending on the specific antenna arrangement required, due to for example, operating frequency, etc., the antenna arrangement (37) may be of the telescoping variety such that it may be extended for greater efficiency as required.

By utilizing the volume (31), that is otherwise ordinarily substantially required by the hinge arrangement (30) alone, for containing and mounting the possibly relatively large antenna arrangement (37), a significant savings in the size of the first housing (13) and/or second housing (15) may be realized. The instant invention may thus be advantageously utilized to reduce the physical size of portable communications devices.

rang ki Ki bahar wilika sanggalalika i bira

10

Claims -

- 1 A portable communications device comprising in combination:
- 5 wireless radio circuitry for processing a radio frequency signal;

first and second housings arranged and constructed for cooperatively containing said wireless radio circuitry, said first and second housing respectively including a first surface and a second surface disposed along an axis;


hinge means, encompassing a volume disposed along said axis, for pivotally connecting said first and said second surfaces such that said second surface pivots about said axis between a first position and a second position, wherein said first position allows substantially enhanced access to said first surface; and

antenna means, disposed within said volume, for coupling said radio frequency signal to said wireless radio circuitry.

- 2 A portable communications device in accordance with claim 1 wherein said first surface includes first means for user interface to said wireless radio circuitry.
- A portable communications device in accordance with claim 2 wherein said second surface includes second means for user interface to said wireless radio circuitry.
- A portable communications device in accordance with claim 1 wherein said antenna means is arranged in a telescopic fashion so as to provide greater efficiency when extended.
 - A portable communications device in accordance with claim 1 wherein said antenna means is inductively coupled to said wireless radio circuitry.
 - A portable communications device in accordance with claim 5 wherein said antenna means is arranged in a telescopic fashion so as to provide greater efficiency when extended.
 - 7 A portable communications device in accordance with claim 1 wherein said second surface is pivoted through an angle of up to 180° when going from said first position to said second position.

ur ubuzra te piko

Barrell Commencer



INTERNATIONAL SEARCH REPORT

International application No. PCT/US92/10351

	COLET O LETT ONLONG THE THE COLET					
A. CLASSIFICATION OF SUBJECT MATTER						
IPC(5) :H04B 1/08 US CL :455/351						
According to International Patent Classification (IPC) or to both national classification and IPC						
7.7.	DS SEARCHED					
	ocumentation searched (classification system followed	t by classification symbols)				
		by classification symbols)				
U.S. :	455/89,90,128,129,347,343/702,856	•				
Documentat	ion searched other than minimum documentation to the	extent that such documents are included	in the fields are all od			
Doodinional	to the state of th	catem that such documents are included	in the neios searched			
			•			
Electronic d	ata base consulted during the international search (na	me of distribution and subsequentially				
Licentific		ine of data base and, where practicable,	, search terms used)			
C. DOC	UMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.			
Y	US,A, 4,126,863 (Ko1waite) 21 Nove	mbor 1078 and and 15 25	1.4			
<u>X</u> Y	60.	1,4				
•	00.		and 7			
			2-3 and			
*			5-6			
Y	IIC A A 002 700 (Comp.) 12 Feb	1001				
1	US,A, 4,992,799 (Garay) 12 February	1991 see col. 1, lines 45-65.	1-7			
v	TIC A A 100 010 OT 1 > 05 D	1070	_			
Y	US, A, 4,180,819 (Nakano) 25 Decemb	per 1979 see col. 4 lines 4-20.	5			
		그리스 공유원활동 사람들이다.				
	그림에는 그는 그들은 이 상황에 가장 그림에 가장 하는 것이 되었다. 그 생생은 그 그 발생이 살았습니다. 사람들은 것이 되었다. 그림을 가장 하는 것이 되었다.		, (0)			
	And the second of the second o		·			
Furth	er documents are listed in the continuation of Box C	. See patent family annex.				
	cial categories of cited documents:	"T" later document published after the inte date and not in conflict with the applic				
	nument defining the general state of the art which is not considered be part of particular relevance	principle or theory underlying the inv	ention			
"E" car	iier document published on or after the international filing date	"X" document of particular relevance; the considered novel or cannot be considered.	e claimed invention cannot be			
	nument which may throw doubts on priority claim(s) or which is	when the document is taken alone	m maniae mi macunice sich			
	ed to establish the publication date of another citation or other cital reason (as specified)	"Y" document of particular relevance; the	e claimed invention cannot be			
	cument referring to an oral disclosure, use, exhibition or other	considered to involve an inventive combined with one or more other suc	h documents, such combinate o			
	ans	being obvious to a person skilled in the				
	priority date claimed	*&* document member of the same patent	family			
Date of the	actual completion of the international search	Date of mailing of the international sea	arch report			
17 FEDD1	JARY 1993	20 APR 1993				
I/ FEDR	JIM \$ 1773					
	nailing address of the ISA/US	Authorized officer M. Mille	ي			
Box PCT	ner of Patents and Trademarks	Land Land Land Land Land Land Land Land				
_	a, D.C. 20231	[
	o. NOT APPLICABLE	Telephone No. (703) 305-4385				
rom PCI/L	SA/210 (second sheet)(July 1992)*	9 * * *	•			

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.